









COSHH RISK ASSESSMENT RECORD

MATERIAL SAFETY DATA SHEETS FOR ALL SUBSTANCES USED ARE LOCATED AT M W CRIPWELL HEAD OFFICE.

PRODUCT NAME	Treflex cutting compound		
MANUFACTURER	Spencer Coatings Ltd	PRODUCT CODE	06PTREF
Manufacturer Contact Number	01224 788400	CAS Ref .	64-17-5
LOCATION(S) OF USE	Mansfield Community Hospital OPD and Holbeck wards	DESCRIPTION	Cutting compound for threading galvanised Steel conduit
MSDS HELD	YES	DATE of MSDS	
	HAZARD CLASSIFICATION (Tick as appropriate)		
	Irritant <input type="checkbox"/>	Corrosive <input type="checkbox"/>	None significant <input checked="" type="checkbox"/>
	Toxic <input type="checkbox"/>	Very Toxic <input type="checkbox"/>	Harmful <input type="checkbox"/>
	Flammable <input type="checkbox"/>	Explosive <input type="checkbox"/>	Dangerous to the Environment <input type="checkbox"/>
		Oxidising <input type="checkbox"/>	
	HOW IS IT USED ? (Describe the process, quantities used, maximum temperatures reached, exposure periods) Treflex is applied to the conduit before a threading die is introduced to provide a threaded end to the conduit. Excessive heat should be avoided,		
	ARE ANY HAZARDOUS SUBSTANCES PRODUCED BY ANY PROCESS (eg fumes from heating a substance) Toxic fumes may be produced in event of combustion		
	WHO MIGHT IT EFFECT ? (Consider not only those using it, but also visitors, those working near by etc) M W C employees and persons in the immediate vicinity		
	WHAT CONTROLS ARE CURRENTLY IN PLACE ?		
	Total enclosure of process <input type="checkbox"/>	Partial enclosure of process <input type="checkbox"/>	General workplace ventilation <input checked="" type="checkbox"/>
	Wet methods (to control dust) <input type="checkbox"/>	Respiratory Protection <input type="checkbox"/>	Eye Protection <input checked="" type="checkbox"/>
	Gloves <input checked="" type="checkbox"/>	Protective Overalls <input checked="" type="checkbox"/>	Other Please specify <input type="checkbox"/>
	GENERAL PRECAUTIONS & PERSONAL PROTECTION NEEDED (Consider warning signs, ventilation, work patterns, personal hygiene / cleanliness, protective clothing) Mopping material preferably fabric should be used to remove excess product.		

